



X2 pro 7 with 2 Ethernet 7" HMI with iX runtime

800 × 480 pixel (16:9)
TFT-LCD touch screen
1.5 GB application memory
Ethernet 2x100 Mbit
-10°C to +60°C operating temperature
CE, FCC, KCC, UL approvals
DNV, KR, GL, LR, ABS, CCS marine approvals

Facts

General description

Part number	630009405
Part status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201
Marine	DNV, KR, GL, LR, ABS, CCS

Mechanical

Mechanical size	204 x 143 x 50mm
Mounting option	Panel Mount, VESA 75 x 75
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	189 x 128mm
Weight	0.8 kg
Housing material	Powder-coated aluminum, Gray

Power

Input voltage	24 V DC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class II power supplies.
Power consumption (max)	14.4W
Input fuse	Internal DC fuse

System

CPU	i.MX6DualLite, Dual Cortex-A9 1.0GHz 512kBL2cache
RAM	1 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Display

Size diagonal	7" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	350 cd/m2
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Communication serial

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS485 (only if COM 2 is RS485)

Ethernet communication

Number of ethernet ports	2
Ethernet port 1	1x10/100 Base-T (shielded RJ45)
Ethernet port 2	1x10/100 Base-T (shielded RJ45)

Expansion interface

Expansion port	Yes, ciX expansion module
SD card	SD and SDHC
USB	1xUSB 2.0 500mA

Environmental

Operating temperature	-10°C to +60°C
Storage temperature	-20°C to +70°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed

Drivers

ABB - COMLI Master (5.7.2)
ABB - COMLI Slave (4.11.0)
ABB - TotalFlow (5.2.1)
Allen Bradley - ControlLogix Ethernet IP (4.24.1)
Allen Bradley - DF1 (5.8.0)
Allen Bradley - DH485 (4.6.2)
Allen Bradley - MicroLogix Ethernet (5.6.0)
Allen Bradley - SLC5/PLC5 Ethernet (5.4.0)
Altus - Alnet I (5.8.0)
Animatics - SmartMotor (5.2.1)
Beckhoff - ADS (5.12.1)
Beckhoff - ADS Symbolic (4.7.0)
Beijer Electronics - iX Demo (4.4.0)
Bernecker + Rainer - Mininet (5.6.0)
BoschRexroth - IndraDrive C (5.2.1)
CAN - FreeCan (J1939/NMEA2000) (5.3.5)
CAN - CANopen (5.4.0)
CODESYS - ARTI v2.x, v3.x (4.8.0)
CODESYS - SoftControl Direct Access (4.4.0)
Cognex - InSight (5.2.2)
Control Techniques - Unidrive (5.3.1)
CTC - Serial Binary (5.4.2)
Delta - PLC Modbus ASCII (5.6.0)
Emerson - Modbus Master RTU/ASCII (5.4.0)
Eurotherm - Easy Serial 631 (5.1.1)
Fatek - Facon (5.10.0)
Galil - DMC (5.2.2)
GE Fanuc - Ethernet SRTP (5.5.0)
GE Fanuc - SNPX (5.6.1)
Gidding & Lewis - Motion control (5.4.0)
IAI - Xsel (5.4.1)
Idec - Computer Link (5.8.0)
Johnson Control - JCONTROL (5.2.1)
KEB - COMBIVERT (5.4.0)
Keyence - KV-series (5.6.0)
Koyo - DirectNET (5.5.0)
Koyo - K Sequence (5.3.1)
Lenze - LECOM A/B (5.6.0)

LS Industrial System - Glofa (5.3.0)
LS Industrial System - Master K (5.4.0)
Matsushita - MEWTOCOL-COM (5.9.2)
Mitsubishi Electric - Alpha2 (5.7.0)
Mitsubishi Electric - A-series (C24) (5.6.0)
Mitsubishi Electric - A-series (CPU) (5.10.0)
Mitsubishi Electric - A-series (E71) (5.4.0)
Mitsubishi Electric - Freqrol FR-A PLC (5.8.2)
Mitsubishi Electric - FX Series ADP/BD (5.10.0)
Mitsubishi Electric - FX Series ENET (5.4.1)
Mitsubishi Electric - FX Series Serial (5.16.0)
Mitsubishi Electric - MC Protocol (5.11.4)
Mitsubishi Electric - MR-J2/MR-J3-T MELSERVO (5.9.0)
Mitsubishi Electric - QnA/Qnn Serial (5.10.0)
Mitsubishi Electric - QnA/Qnn (C24) (5.5.0)
Mitsubishi Electric - Q-Series Ethernet (E71) (5.5.0)
Modicon - Modbus Master (5.19.4)
Modicon - Modbus Slave RTU/TCP (4.20.2)
NEMA0183 - NEMA 0183 (4.6.0)
Omron - Ethernet IP (4.3.3)
Omron - FINS (5.9.5)
Omron - Host Link (5.6.0)
Regin - EXOline (5.3.2)
Profibus - Profibus DP (5.5.1)
SAIA - S-BUS Serial/Ethernet (5.7.0)
Schneider Electric - Modbus (5.3.0)
Schneider Electric - TSX Uni-Telway (4.5.3)
Siemens - S5 PG/AS511 (5.4.0)
Siemens - S7 200 PPI (5.8.5)
Siemens - S7 over TCP (S7-200/300/400/1200/1500) (4.18.0)
Siemens - MPI (HMI Adapter) (5.7.0)
Siemens - MPI (CiX) (5.3.0)
WAGO - Modbus TCP (5.10.0)
Vigor - M/VB-Series (5.6.0)
Yamaha - VIP (5.2.1)
Yaskawa - Memobus Master (5.7.0)
Yokogawa - FA-M3 (5.6.0)

BASIC JAPAN

Basic Japan株式会社 Suginami Tokyo, Japan
Phone: 03-5335-7651
E-mail: mail@basicjp.com
URL: www.basicjp.com