

DuraPANEL LED 24" WS



Dura PANEL LED パネルPCは、風力発電・船舶等の用途に開発された頑健な構造を持つ製品です。

- 広い範囲の温度下で使用可能
 - 耐振動
 - ISIC 社伝統の高い信頼性
 - 少ない稼働休止時間
 - フレキシビリティに富んだ構造
 - 設置のしやすさ
 - 頑健でコンパクトなデザイン
 - 低消費電力
- CPU: Intel® Core i3-3220T 2,8GHz (Ivy Bridge) / Celeron® G465 -1,9 GHz
 - Intel® HD 2500 強力な On-Board Graphics
 - Max 8GB DDR3 RAM
 - Dual Intel® LAN
 - Intel® Advanced Network Services
 - バックライト調光機能
 - ファンレスで耐熱デザインを実現
 - 貴社独自のカスタマイズ可能

Specifications

DuraPANEL - General

CPU:	Intel® Celeron® Processor G465 – 1,9 GHz single core, Two Threads, <i>Optional Intel® Core i3-3220T 2,8 GHz – Two cores, 4 threads (CPUMark 3,984)</i> <i>Optional Intel® Core i7-3770T 2,5 GHz – Four cores, 8 threads (CPUMark 9,010)</i>
Chipset:	Intel® Q77 Express Chipset
メモリ:	1GB DDR3 1333MHz SDRAM <i>Up to 8GB DDR3 SDRAM (option)</i>
ハードディスクドライブ:	32GB SSD SATA rated <i>Optional 64/128/256 GB SSD SATA or USB (option)</i>
ビデオ:	Intel® HD 2500 Graphics controller on-CPU <i>DirectX* 11 and OpenGL 3.0 compliant</i> <i>Dual Independent display capable</i>
External Video out:	DisplayPort and HDMI video output connectors
オーディオ:	6-channel (4+2) Intel® High Definition Audio, Realtek ALC892 audio codec. 8-channel (7.1) Intel HD Audio via DisplayPort
Ethernet:	2 x 10/100/1000 Gbits/s Ethernet LAN on-board, (RJ45) <i>1 x Intel® 82579LM Gigabit Ethernet Controller (red connector)</i> <i>1 x Intel® 82574L Gigabit Ethernet Controller (black connector)</i>
Ports:	2 x 3,5mm Minijack, 1x RS-232 (on internal Header)
USB:	4 x USB 3.0 ports, plus 8 USB 2.0 internally available
Expansion Slots:	1 x PCI Express Half-mini Card Slot 1 x PCI Express Full-/ Half- Mini Card Slot

DuraPANEL - Front

Display size:	23.6 inch 16:9 LCD (TFT)
Resolution:	1920 x 1080
Active area:	521 x293 mm
View angle:	88°(T/B), 88°(L/R) (typical)
Luminance:	250 Cd/m² (typical)
Contrast ratio:	1000:1 (typical)
Front glass:	Anti glare Hardness 3H
Protection:	IP65 (flush mount)

DuraPANEL - Power

スタンダード: 90-264Vac. 50-60Hz Input/ 18-36Vdc Input

DuraPANEL - Environmental

Operating Temperature:	-15 to 55 °C
Storage Temperature:	-25 to 70 °C
相对湿度:	8 to 90 %

DuraPANEL - Approvals

CE Mark:	EN61000-6-2
Marine:	IACS E10 Rev.5 & IEC 60945 Ed.4

DuraPANEL - Dimensions

Size:	601(W) x 408mm (H) x 68mm (D)
Weight:	App. 12 kg.
Brackets	Desk/ceiling-and wall-bracket with IP 22 rear-cover available (optional extra)

BASIC JAPAN

Basic Japan 株式会社 Mitaka-City, Tokyo Japan

Phone : 0422-29-9875 Fax : 0422-29-9877

E-mail : mail@basicjp.com